

S1-C5F [Cu-50hz]

● Technical Specifications

- Capacity : 100VA ~ 20kVA
- Primary Voltage : AC 100V~600V
- Secondary Voltage : AC 100V~600V
- Operating Frequency : 60Hz
- Insulation Class : F Class
- Type : TB (Terminal Block) - SINSUENG3



● Specifications

Model.	Specifications			Dimension(mm)							Weight (kg)
	Capa.(VA)	Pri.(V)	Sec.(V)	W	D	H	M1	M2	M3	N	
S1-C5F 100	100	100V ~ 600V	100V ~ 600V	96	96	110	60	80	70	5x16	2.6
S1-C5F 150	150			105	95	120	73	93	70	5x14	3.5
S1-C5F 200	200			105	100	120	73	93	70	5x14	3.9
S1-C5F 300	300			114	124	130	72	102	94	6x20	5.7
S1-C5F 400	400			133.2	115	145	89	119	85	7x20	6.9
S1-C5F 500	500			133.2	125	145	89	119	95	7x20	8
S1-C5F 750	750			152.4	137	160	99	131	108	7x20	8.8
S1-C5F 1K	1K			152.4	137	160	99	131	118	7x20	12.4
S1-C5F 2K	2K			181.2	166	195	122	161	134	7x20	20.9
S1-C5F 3K	3K			219	151	225	165	200	113	7x20	29.4
S1-C5F 5K	5K			243	190	245	150	200	145	10x20	43.9
S1-C5F 7.5K	7.5K			270	174	275	180	230	140	10x20	68.6
S1-C5F 10K	10K			270	204	275	180	230	170	10x20	83.4
S1-C5F 15K	15K			309	210	315	205	-	165	10x25	111
S1-C5F 20K	20k			309	240	315	205	-	195	10x25	131.3

* 당사 표준모델 규격이며, 사양변경 시 사이즈는 변경될 수 있습니다.

* These are our standard model specifications, and sizes may change as specifications change.

● Dimension

