

S1-C6F [Cu-60Hz]

● Technical Specifications

- Capacity : 100VA ~ 20kVA
- Primary Voltage : AC 100V~600V
- Secondary Voltage : AC 100V~600V
- Operating Frequency : 60Hz
- Insulation Class : F Class
- Type : TB (Terminal Block) - SINSUENG3



● Specifications

| Model. | Specifications | | | Dimension(mm) | | | | | | | Weight (kg) |
|-------------|----------------|-------------------|-------------------|---------------|-----|-----|-----|-----|-----|-------|-------------|
| | Capa.(VA) | Pri.(V) | Sec.(V) | W | D | H | M1 | M2 | M3 | N | |
| S1-C6F 100 | 100 | 100V ~ 600V | 100V ~ 600V | 96 | 91 | 110 | 60 | 80 | 65 | 5x16 | 2.3 |
| S1-C6F 150 | 150 | | | 96 | 101 | 110 | 60 | 80 | 75 | 5x16 | 2.9 |
| S1-C6F 200 | 200 | | | 105 | 95 | 120 | 73 | 93 | 70 | 5x14 | 3.5 |
| S1-C6F 300 | 300 | | | 114 | 112 | 130 | 72 | 102 | 82 | 6x20 | 4.6 |
| S1-C6F 400 | 400 | | | 114 | 124 | 130 | 72 | 102 | 94 | 6x20 | 5.7 |
| S1-C6F 500 | 500 | | | 133.2 | 115 | 145 | 89 | 119 | 85 | 7x20 | 6.7 |
| S1-C6F 750 | 750 | | | 133.2 | 125 | 145 | 89 | 119 | 95 | 7x20 | 6.7 |
| S1-C6F 1K | 1K | | | 152.4 | 137 | 160 | 99 | 131 | 108 | 7x20 | 11 |
| S1-C6F 2K | 2K | | | 181.2 | 146 | 195 | 122 | 161 | 114 | 7x20 | 17 |
| S1-C6F 3K | 3K | | | 219 | 151 | 225 | 165 | 200 | 113 | 7x20 | 28 |
| S1-C6F 5K | 5K | | | 219 | 176 | 225 | 165 | 200 | 138 | 7x20 | 36 |
| S1-C6F 7.5K | 7.5K | | | 270 | 174 | 275 | 180 | 230 | 140 | 10x20 | 60 |
| S1-C6F 10K | 10K | | | 270 | 184 | 275 | 180 | 230 | 150 | 10x20 | 75 |
| S1-C6F 15K | 15K | | | 309 | 190 | 315 | 205 | - | 145 | 10x25 | 100 |
| S1-C6F 20K | 20k | | | 309 | 220 | 315 | 205 | - | 175 | 10x25 | 120 |

* 당사 표준모델 규격이며, 사양변경 시 사이즈는 변경될 수 있습니다.

* These are our standard model specifications, and sizes may change as specifications change.

● Dimension

