

SS3-TNDUCG (UL Certified)

● Technical Specifications


- Capacity : 5kVA ~ 100kVA
- Operating Frequency : 50Hz/60Hz
- Primary Voltage : AC 208V, 220V
- Secondary Voltage : AC 208V, 220V
- Insulation : "H" Class
- Connection : Y-D
- Standard : UL 5085 - 1/2
- UL Approval Number : E533045



● Specifications

Model.	Specifications			Dimension(mm)								Weight (kg)
	Capa.(kVA)	Pri.(V)	Sec.(V)	W	D	H	W1	D1	E	MH		
SS3-TNDUCG 005K	5	208V 220V	208V 220V	420	170	314	300	120	M6	Ø11	57	
SS3-TNDUCG 007.5K	7.5			465	180	354	300	130	M6	Ø11	77	
SS3-TNDUCG 010K	10			465	200	354	300	150	M6	Ø11	95	
SS3-TNDUCG 015K	15			495	210	379	300	160	M6	Ø11	120	
SS3-TNDUCG 020K	20			525	230	404	350	170	M6	Ø11	140	
SS3-TNDUCG 030K	30			525	250	449	350	190	M8	Ø13	180	
SS3-TNDUCG 040K	40			585	250	444	400	190	M8	Ø13	219	
SS3-TNDUCG 050K	50			585	280	504	400	210	M8	Ø13	250	
SS3-TNDUCG 060K	60			585	290	584	400	220	M8	Ø13	315	
SS3-TNDUCG 075K	75			615	300	580	400	230	M8	Ø13	357	
SS3-TNDUCG 085K	85			630	310	590	400	240	M8	Ø13	372	
SS3-TNDUCG 100K	100			675	320	600	450	240	M8	Ø13	428	

● Dimension



● Wiring Diagram

